

KESTREL SERIES

CONVEYOR LIGHT

INTEGRAL E-PACK GREEN EYEWASH DC SOLAR

| | | | | |
|----------------------------|------------------------|------------------------|------------------|--------------------|
| 5 YR WARRANTY | 66 IP RATING | 08 IK RATING | 70 CRI | 140 LM/W |
|----------------------------|------------------------|------------------------|------------------|--------------------|



STANDARD 4000K

- Designed for high-vibration / high-impact areas
- Green eye-wash version for site first-aid
- Solid state integral emergency option, with intelligent controls
- Solar-compatible option for remote sites
- IP66 water and dust-proof
- Better heat dissipation, flicker-free and long-life LED

IDEAL FOR

- Conveyor
- Walkway
- Tunnel
- Roadway
- Industrial
- Mining



GREEN EYEWASH



AMBER



STOCK
Available



| MODEL | POWER | LUMEN | INPUT | BATTERY | CCT / COLOUR |
|------------------------|-------|-------|-------|----------|-------------------------|
| STANDARD SERIES | | | | | |
| ETG-KCL70-4K | 70W | 9800 | AC | - | 4000K (Optional: Amber) |
| ETG-KCL70-EM | 70W | 9800 | AC | Built in | |
| ETG-KCL70-GEM | 70W | - | AC | Built in | Green |
| SOLAR SERIES | | | | | |
| ETG-KCL70-DC | 70W | 9800 | DC | - | 4000K (Optional: Amber) |
| ETG-KCL70-GDC | 70W | - | DC | - | Green |

| | | | |
|------------------------|------------------------|-------------------------|--|
| Luminous Efficacy | 140lm/W | Beam Angle | 140° |
| AC Input | 110 - 265 VAC | Mounting Option (mm) | Horizontal Spigot Mount Ø32-35 & 40-44 |
| DC Input | 9 -32 VDC | CRI | >70 |
| LED Chip | Nichia Osram : Green | IP Rating | IP66 |
| Battery | 4W 3H Battery | IK Rating | IK08 |
| CCT | 4000K (Optional Amber) | Cable Ø / Gland / Cable | 2.5 mm ² - 3 Core cable / M20 / 5m length |
| Operating Temp | -30°C to +50°C | Body | ALU Alloy + PC Lens / Black |
| Input Surge Protection | 20kV SPD | Weight (kg) | 4.7 (Non emergency model) |
| PF | >0.95 | Lifespan | >50,000 (70% Brightness) |
| Driver | Sosen | Warranty | 5 Years (2 Year battery) |



Average: 84lux @ 3m height - 14m gap

Average: 98lux @ 3m height - 12m gap

Average: 146lux @ 3m height - 8m gap

DIMENSIONS

