

RETRO MINI SERIES **G2**

5 YR WARRANTY	66 IP RATING	08 IK RATING	70 CRI	130 LM/W
----------------------------	------------------------	------------------------	------------------	--------------------

- » Cost effective rural roadway lighting
- » New sleek body design
- » IP66, IK08 protection rating
- » 125-130lm/W, IP66, 10KV
- » Optional 3-PIN, 5-PIN and 7-PIN NEMA socket
- » Intelligent function options



Optional Photocell control

IDEAL FOR

- Carparks
- Walkway
- Picnic Areas
- Roadway
- Pathways
- Playgrounds

STOCK
Available



MODEL	ETG-MRSL50-G2		
Power (W)	50		
Lumen (lm)	6,250		
Luminous Efficacy (lm/W)	130		
Weight (kg)	2.5		
Dimensions (mm)	478 × 166 × 81		
Beam angle	Type II Medium		
Colour Temperature	4000K (3000K, 5000K Optional)	Surge Protection	6kV line-line, 10kV line-earth
LED Chips	Seoul Chip	CRI	70 (80 Optional)
Input Voltage	200-240VAC (50/60 Hz)	Optional Controls	Photocell control / 3, 5 and 7-PIN NEMA sockets
Operating Temp	-30°C to + 50°C	Body	Powder coated silver
IP Rating	IP66 Weather resistant	Mounting	4-12m Pole Mount
IK Rating	IK08 Impact resistant	Lifespan	>50,000 (Ta=30°C@L70)
PF	≥0.90	Warranty	5 Years
Driver	Sosen Driver		